

Document Number: 140418JL	Originator: Jon Landau	Date: February 27 th , 2019
---------------------------	------------------------	--

Data Sheet
PG400-UPS-HR-DC24-NB



Document Number: 120514JL	Originator: / Sign:	Approved By: / Sign:
---------------------------	---------------------	----------------------


Warning: This document may contain technical data whose export is restricted by the Arms Export Control Act (Title 22, U.S.C. Sec 2751, et seq.) or the Export Administration Act of 1979, as amended (Title 50, U.S.C., app. 2401 et seq.) Violators of these export laws are subject to sever criminal penalties.
Proprietary Data: The data disclosed in this document was originated in whole or in part by AJPS Inc. and is to be utilized only for the specific purposes for which it was supplied. It is not to be disclosed, transmitted or reproduced without the prior written consent of AJPS Inc.

Creation Date: 07 May 2012	Reference ECO:	Document Number Rev Level: D
----------------------------	----------------	------------------------------

SPECIFICATION	VALUE	UNITS
DC Output		
Rated Voltage	24 +/-2%	Vdc
Rated Max. Current	14.6	Adc
Max. Rated Power	350	Watts
Run Time on External Battery (PG-BAT-EXT)	>70 @ 25°C, 80% Load (zero output below 0C)	Minutes
Transfer Time to Battery	Instant, On-Line conversion	
AC Input		
Voltage Range (Universal)	100 - 240	Volts AC
Frequency Range	47 - 63	Hertz
Nominal Current	<4 @ 120Vac	Amps AC
Inrush Current (typical)	40	Amps AC
Efficiency (typical)	≥80	%
Power Factor (typical)	>0.95	
Leakage Current	<3 @ 120Vac	mAmps AC
Conversion	Double, On-Line	
Isolation		
AC Input to DC Output	Yes	
Internal Battery Module		
Not Applicable		
Protection		
Over Load	Yes	
Output Short Circuit	Yes	
Over Temperature	Yes	
AC Input Protection	Yes	

SPECIFICATION	VALUE	UNITS
SNMP v3		
	AC Input present, DC Input Present, DC Output Active, Over Temperature	
Front Panel Indicators		
Power LED	Green=Unit On	
Alarm Disabled LED	Red=Alarm Disabled	
Front Panel Control		
On/Off Switch	When On, enables UPS output, when in off position, no DC output is present	
Audible Alarm	Toggle switch, up enables audible alarm, down disables	
Connectors		
DC Output	1 x MS3102E20-4S, Pin A,B= +Vout, Pin C,D= Return	J2
AC Input	1 x MS3102E16-10P Pin A= Line, Pin B=Ground, Pin C =Neutral	J1
DC Input	1 x MS3102E16-11P, Pin A=+Vin, Pin B=Vin RTN	J4
Ethernet Port	Standard RJ-45	J3
Safety Ground	¼ -20 Stud (Rear Panel)	
Environmental		
Operating Temperature Range	-20 to +55*	°C
Storage Temperature Range	-40 to +70*	°C
Operating Humidity	95 non-condensing*	%
Altitude	10, 000 (Operating) / 40,000 (Non-Operating)*	feet
Fungus	No fungus promoting materials used	
Sand and Dust	MIL-STD-810G* (Front panel re-useable filter installed)	
Vibration	MIL-STD-810G *	
Functional Shock	MIL-STD-810G *	
Other Specifications		
Startup Time	<30	Seconds
Cooling	Front Panel Intake & Rear Exhaust Airflow	
	* Designed to meet, formal report requires lab testing at additional expense	


SPECIFICATION	VALUE	UNITS
Physical Properties		
Dimensions	1.74H x 8.81W x 13D	inch
Mounting	1U Height, 14 Inch Depth, Half Rack	
Mounting Hardware	Hinged Rear Brackets	
Weight	10.0	lbs.
Material	Aluminum	
Color/Finish	Black #F63-B70 / Light Texture	



PG400-UPS-HR-DC24-NB
Front View



PG400-UPS-HR-DC24-NB
Rear View



PG400-UPS-HR-DC28
Mechanical Drawing