

AJPS INC.
6931 Land O Lakes Blvd
Land O Lakes FL 34638
813-996-2583

Doc. Name: PG1500-UPS-4N

Form Number: 690-0940-00

Document Number: 130211JL-1

Originator: Mike Henderson

Date: April 30, 2020

Data Sheet

PG1500-UPS-4N-3P



Document Number: 130211JL-1

Originator: / Sign:

Approved By: / Sign:

Warning: This document may contain technical data whose export is restricted by the Arms Export Control Act (Title 22, U.S.C. Sec 2751, et seq.) or the Export Administration Act of 1979, as amended (Title 50, U.S.C., app. 2401 et seq.) Violators of these export laws are subject to severe criminal penalties.
Proprietary Data: The data disclosed in this document was originated in whole or in part by AJPS Inc. and is to be utilized only for the specific purposes for which it was supplied. It is not to be disclosed, transmitted or reproduced without the prior written consent of AJPS Inc.

Creation Date: 07 May 2012

Reference ECO:

Document Number Rev Level:

Page 2 of 6

SPECIFICATION	VALUE	UNITS
Front Panel Indicators		
Battery Status	Green=Charged, Yellow=Charging, Red=Discharging	
Switch LED	Green=Unit On (Output enabled)	
Front Panel Control		
On/Off Switch	When on, enables UPS output	
Alarm Disable	Enable/disable the audible alarm sounder	
SNMP v3		
	AC Input present, BXM Input present, Battery Status (charged, charging, discharging), AC Output Active, Over Temperature	
Rear Connectors		
AC Output	4 x NEMA 5-15/20R receptacles	J2
AC Input	MS3102E18-11P	J1
Ethernet	RJ-45, standard Ethernet pin out (SNMP communications)	J4
Safety Ground Stud	¼ -20 Stud (Rear Panel)	
Protection		
Over Load	Yes	
Output Short Circuit	Yes	
Over Temperature	Yes	
AC Input Protection	Yes	
Isolation		
AC Input to AC Output	Yes	
BXM Input to AC Output	Yes	
Physical Properties		
Dimensions	1.74H x 17.10W x 23.00D	inch
Mounting	1U 19 Inch Rack (adjustable mounting depth)	
Weight	</=27	lbs.
Material	Aluminum	
Color/Finish	Gray	

SPECIFICATION	VALUE	UNITS
Environmental		
Operating Temperature Range	−20 to +50*	°C
Storage Temperature Range	−40 to +65*	°C
Working Humidity	95 non-condensing*	%
Altitude	10, 000 (Operating) / 40,000 (Non-Operating)*	feet
Fungus	MIL-STD-810G, method 508*	
Vibration	MIL-STD-810G*	
Functional Shock	MIL-STD-810G*	
	* Designed to meet, lab testing required for formal certification	




Air Intake Alarm Disable Output Enable Air Intake Battery Module

PG1500-UPS-4N-3P
Front View



Ground Stud Air Exhaust AC Output AC Input Ethernet Port Air Exhaust AC Output

PG1500-UPS-4N-3P
Rear View



PG1500-UPS-4N-3P
Mechanical Drawing