

Document Number: 130211JL-1

Originator: Jon Landau

Date: May 15th, 2019

Data Sheet

PG1500-UPS-V3-3P-IEC



Document Number: 130211JL-1

Originator: / Sign:



Approved By: / Sign:


Warning: This document may contain technical data whose export is restricted by the Arms Export Control Act (Title 22, U.S.C. Sec 2751, et seq.) or the Export Administration Act of 1979, as amended (Title 50, U.S.C., app. 2401 et seq.) Violators of these export laws are subject to severe criminal penalties.
Proprietary Data: The data disclosed in this document was originated in whole or in part by AJPS Inc. and is to be utilized only for the specific purposes for which it was supplied. It is not to be disclosed, transmitted or reproduced without the prior written consent of AJPS Inc.

SPECIFICATION	VALUE	UNITS
AC Output		
Rated Voltage	120 Pure Sine Wave ($\pm 5\%$)	Volts
Frequency	60 ($\pm 0.25\%$)	Hertz
Rated Max. Current	10	Amps
Maximum Rated Power	1500VA (0.8PF), 1200W (w/resistive load)	
Phase	Single	
Total Harmonic Distortion	<5 (w/resistive load)	%
Run Time on Battery	>12 (at 25°C, 80% Load, zero at or below 0C)	Minutes
Transfer Time to Battery	Instant, On-Line conversion	
AC Input		
Voltage Range	208(Line to line), 3 Phase WYE	Volts AC
Frequency Range	47 – 63	Hertz
Nominal Current	~4@208V per phase	Amps AC
Inrush Current (typical)	100 (maximum)	Amps AC
Power Factor (typical)	>0.8	
Leakage Current	<4.0	mAmps AC
Efficiency (typical)	>80 (AC Input to AC Output)	%
Conversion	Double On-Line	
Battery		
Rating	48	Vdc
Type	Lithium Iron Phosphate	
Hot-Swappable	Yes (when on AC Input)	
Replacement Time	Less than one minute	
Recharge Time	6 Hours to 95% after full discharge	
BXM Input		
	(PG-BXM-48)	
Voltage Range	41 - 48	Vdc
Nominal Voltage	48	Vdc
Efficiency (typical)	>84	%
Conversion	Single	

SPECIFICATION	VALUE	UNITS
Front Panel Indicators		
Battery Status	Green=Charged, Yellow=Charging, Red=Discharging	
Switch LED	Green=Unit On	
Front Panel Control		
On/Off Switch	When on, enables UPS output	
Alarm Disable	Enable/disable the audible alarm sounder	
SNMP v3		
	AC Input present, Battery Status (charged, charging, discharging), AC Output Active, Over Temperature	
Rear Connectors		
AC Output	2 x Locking IEC320/C13 Receptacles	J2
AC Input	1 x MS3102E16S-8P, Pin A=Phase A, Pin B=Phase B, Pin C=Phase C, Pin D=Neutral, Pin E= Earth Ground	J1
AC Load Share*	Type MS3102E16-10S	J3
	Pin A = Line, Pin B = Ground, Pin C = Neutral	
Load Share Interface*	Female Sub-D 9 Pin	J4, J5
	* Allows units to be stacked for increase in power handling capability, provides synchronization between units (not used in single UPS installation)	
Ethernet	RJ-45, standard Ethernet pin out (SNMP v3 communications)	J6
Emergency Cutoff	MS3102E12S-3S, Pin A = +V, Pin B = -V Contact closure Closed = output enabled, Open via external switch = output disabled	J8
BXM Input	MS3102E20-23P, Pin A = +Vin, Pin B = -Vin (only used when PG-BXM is present)	J7
Safety Ground Stud	¼ -20 Stud (Rear Panel)	
Protection		
Over Load	Yes	
Output Short Circuit	Yes	
Over Temperature	Yes	
AC Input Protection	Yes	
DC BXM Input Protection	Yes	
Isolation		
AC Input to AC Output	Yes, Double	
BXM Input to AC Output	Yes, Double	

SPECIFICATION	VALUE	UNITS
Environmental		
Operating Temperature Range	–20 to +50*	°C
Storage Temperature Range	–40 to +72*	°C
Working Humidity	95 non-condensing*	%
Altitude	10,000 (Operating) / 40,000 (Non-Operating)*	feet
Fungus	MIL-STD-810G, method 508*	
Sand and Dust	MIL-STD-810G* (w/Optional Filters)	
Vibration	MIL-STD-810G*	
Functional Shock	MIL-STD-810G*	
	* Designed to meet, lab testing required.	
Physical Properties		
Dimensions	1.729H x 17.1W x 23D	inch
Mounting	1U 19 Inch Rack (adjustable mounting depth)	
Weight	27	lbs.
Material	Aluminum	
Color/Finish	Gray	





Mechanical Drawing